



XMPP

XEP-0086: Error Condition Mappings

Robert Norris
<mailto:rob@cataclysm.cx>
<xmpp:rob@cataclysm.cx>

Peter Saint-Andre
<mailto:peter@andyet.net>
<xmpp:stpeter@stpeter.im>
<https://stpeter.im/>

2004-02-17
Version 1.0

| Status | Type | Short Name |
|------------|---------------|------------|
| Deprecated | Informational | N/A |

A mapping to enable legacy entities to correctly handle errors from XMPP-aware entities.

Legal

Copyright

This XMPP Extension Protocol is copyright © 1999 – 2017 by the [XMPP Standards Foundation](#) (XSF).

Permissions

Permission is hereby granted, free of charge, to any person obtaining a copy of this specification (the "Specification"), to make use of the Specification without restriction, including without limitation the rights to implement the Specification in a software program, deploy the Specification in a network service, and copy, modify, merge, publish, translate, distribute, sublicense, or sell copies of the Specification, and to permit persons to whom the Specification is furnished to do so, subject to the condition that the foregoing copyright notice and this permission notice shall be included in all copies or substantial portions of the Specification. Unless separate permission is granted, modified works that are redistributed shall not contain misleading information regarding the authors, title, number, or publisher of the Specification, and shall not claim endorsement of the modified works by the authors, any organization or project to which the authors belong, or the XMPP Standards Foundation.

Warranty

NOTE WELL: This Specification is provided on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE.

Liability

In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall the XMPP Standards Foundation or any author of this Specification be liable for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising from, out of, or in connection with the Specification or the implementation, deployment, or other use of the Specification (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if the XMPP Standards Foundation or such author has been advised of the possibility of such damages.

Conformance

This XMPP Extension Protocol has been contributed in full conformance with the XSF's Intellectual Property Rights Policy (a copy of which can be found at <https://xmpp.org/about/xsf/ipr-policy>) or obtained by writing to XMPP Standards Foundation, P.O. Box 787, Parker, CO 80134 USA).

Contents

| | | |
|---|-------------------------------|---|
| 1 | Introduction | 1 |
| 2 | Supporting Legacy Entities | 1 |
| 3 | Implementing Legacy Protocols | 2 |
| 4 | Conclusion | 3 |

1 Introduction

XMPP Core ¹ documents formats and semantics for stanza error responses. The XML of these errors is different from that of errors that have been traditionally used on the Jabber network. Until such time that all entities support these new XMPP-style errors, there is a need for entities to issue errors that are understandable by both legacy and XMPP-compliant entities. This document outlines an appropriate mapping to allow this to occur. This document can also be used by implementers of legacy protocols to determine which XMPP-style error should be used when only a legacy error code is documented.

2 Supporting Legacy Entities

XMPP-compliant entities can issue errors to legacy clients and servers by adding a "code" attribute to the <error/> element it sends.

Listing 1: A simple error response

```
<message
  to='juliet@capulet.com/balcony'
  from='romeo@montague.net/garden'
  type='error'>
  <body>Wherefore art thou, Romeo?</body>
  <error code='404' type='cancel'>
    <item-not-found xmlns='urn:ietf:params:xml:ns:xmpp-stanzas' />
  </error>
</message>
```

Legacy entities receiving this error will use the "404" to determine what happened, while XMPP-compliant entities will use the error type and the child element that specifies the condition.

XMPP-compliant entities should add the following error codes to errors if they want them to be understood by legacy entities:

| XMPP error condition | XMPP error type | Legacy error code |
|----------------------------|-----------------|-------------------|
| <bad-request/> | modify | 400 |
| <conflict/> | cancel | 409 |
| <feature-not-implemented/> | cancel | 501 |
| <forbidden/> | auth | 403 |
| <gone/> | modify | 302 (permanent) |
| <internal-server-error/> | wait | 500 |
| <item-not-found/> | cancel | 404 |

¹RFC 6120: Extensible Messaging and Presence Protocol (XMPP): Core <<http://tools.ietf.org/html/rfc6120>>.

| XMPP error condition | XMPP error type | Legacy error code |
|----------------------------|-----------------|-------------------|
| <jid-malformed/> | modify | 400 |
| <not-acceptable/> | modify | 406 |
| <not-allowed/> | cancel | 405 |
| <not-authorized/> | auth | 401 |
| <payment-required/> | auth | 402 |
| <recipient-unavailable/> | wait | 404 |
| <redirect/> | modify | 302 (temporary) |
| <registration-required/> | auth | 407 |
| <remote-server-not-found/> | cancel | 404 |
| <remote-server-timeout/> | wait | 504 |
| <resource-constraint/> | wait | 500 |
| <service-unavailable/> | cancel | 503 |
| <subscription-required/> | auth | 407 |
| <undefined-condition/> | [any] | 500 |
| <unexpected-request/> | wait | 400 |

3 Implementing Legacy Protocols

Implementors of legacy protocols should use the appropriate XMPP-style error alongside a legacy error code as specified in the following table:

| Legacy error code | Meaning | XMPP error condition | XMPP error type |
|-------------------|------------------|--|-----------------|
| 302 | Redirect | <redirect/> (temporary) or <gone/> (permanent) | modify |
| 400 | Bad Request | <bad-request/> See also the <jid-malformed/> and <unexpected-request/> stanza errors. | modify |
| 401 | Not Authorized | <not-authorized/> See also the <not-authorized/> stream error. | auth |
| 402 | Payment Required | <payment-required/> | auth |
| 403 | Forbidden | <forbidden/> | auth |

| Legacy error code | Meaning | XMPP error condition | XMPP error type |
|-------------------|-----------------------|--|-----------------|
| 404 | Not Found | <item-not-found/> See also the <remote-server-not-found/> | cancel |
| 405 | Not Allowed | stanza error. <not-allowed/> | cancel |
| 406 | Not Acceptable | <not-acceptable/> See also the <unexpected-request/> stanza error. | modify |
| 407 | Registration Required | Re- <registration-required/> | auth |
| 408 | Request Timeout | <remote-server-timeout/> | wait |
| 409 | Conflict | <conflict/> | cancel |
| 500 | Internal Server Error | <internal-server-error/> See also the <undefined-condition/> stanza error. | wait |
| 501 | Not Implemented | <feature-not-implemented/> | cancel |
| 502 | Remote Server Error | <service-unavailable/> | wait |
| 503 | Service Unavailable | <service-unavailable/> | cancel |
| 504 | Remote Server Timeout | <remote-server-timeout/> | wait |
| 510 | Disconnected | <service-unavailable/> | cancel |

4 Conclusion

Mapping legacy error codes to XMPP-style errors is an inexact science, and there are likely to be inconsistencies in some places. However, it is the authors' belief that the mapping presented in this document will be adequate for the majority of cases, and will help smooth the migration to XMPP-compliant implementations.