

# XEP-0125: vCard Infobits Mapping

Peter Saint-Andre
mailto:stpeter@stpeter.im
xmpp:stpeter@jabber.org
https://stpeter.im/

2003-12-15 Version 0.1

StatusTypeShort NameRetractedInformationalN/A

NOTE: This proposal was retracted by the author on 2004-02-19.

## Legal

### Copyright

This XMPP Extension Protocol is copyright © 1999 – 2024 by the XMPP Standards Foundation (XSF).

#### Permissions

Permission is hereby granted, free of charge, to any person obtaining a copy of this specification (the "Specification"), to make use of the Specification without restriction, including without limitation the rights to implement the Specification in a software program, deploy the Specification in a network service, and copy, modify, merge, publish, translate, distribute, sublicense, or sell copies of the Specification, and to permit persons to whom the Specification is furnished to do so, subject to the condition that the foregoing copyright notice and this permission notice shall be included in all copies or substantial portions of the Specification. Unless separate permission is granted, modified works that are redistributed shall not contain misleading information regarding the authors, title, number, or publisher of the Specification, and shall not claim endorsement of the modified works by the authors, any organization or project to which the authors belong, or the XMPP Standards Foundation.

#### Warranty

**##** NOTE WELL: This Specification is provided on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDI-TIONS OF ANY KIND, express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. **##** 

#### Liability

In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall the XMPP Standards Foundation or any author of this Specification be liable for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising from, out of, or in connection with the Specification or the implementation, deployment, or other use of the Specification (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if the XMPP Standards Foundation or such author has been advised of the possibility of such damages.

#### Conformance

This XMPP Extension Protocol has been contributed in full conformance with the XSF's Intellectual Property Rights Policy (a copy of which can be found at <a href="https://xmpp.org/about/xsf/ipr-policy">https://xmpp.org/about/xsf/ipr-policy</a> or obtained by writing to XMPP Standards Foundation, P.O. Box 787, Parker, CO 80134 USA).

## Contents

| 1 | Introduction   | 1                  |
|---|--|--------------------|
| 2 | vCard Mapping  | 1                  |
| 3 | Supplementing vCard  | 4                  |
| 4 | Security Considerations  | 5                  |
| 5 | IANA Considerations  |                    |
| 6 | <ul> <li>XMPP Registrar Considerations</li> <li>6.1 vCard Mapping Infobits</li> <li>6.2 vCard Supplement Infobits</li> </ul> | <b>5</b><br>6<br>6 |

### 1 Introduction

Infobits (XEP-0120)<sup>1</sup> defines a protocol for capturing granular information (or "infobits") about users, servers, services, rooms, nodes, commands, files, and other phenomena on the Jabber/XMPP network; however, that document defines the protocol only, not the infobits themselves. This document specifies how to encapsulate one sort of metadata in infobits: the metadata elements about entities defined by RFC 2426<sup>2</sup> (supplemented by vCard-like metadata that is not defined in RFC 2426), thus enabling the Jabber community to supersede vcard-temp (XEP-0054)<sup>3</sup>. Note well that this document is decidedly *not* meant to provide an exhaustive catalog of possible infobits. Future registrations, whether in XMPP Extension Protocol specifications or direct submissions to the XMPP Registrar<sup>4</sup>, will specify additional infobits.

### 2 vCard Mapping

In order to supersede the vCard-XML protocol currently in use within the Jabber community, it is necessary to define infobits that correspond to the data elements defined by the vCard-XML DTD (more precisely, the vCard Profile Features specified in section 3 of RFC 2426). These are shown in the following table. (Note: this mapping uses the vCard entity names specified in draft-dawson-vcard-xml-dtd-03<sup>5</sup>, not those specified in XEP-0054.)

| Infobit Key | vCard Element  | Comments  |
|-------------|----------------|---|
| birthdate   | bday (partial) | Date of birth (DD); prepend with birthyear and birthmonth (with "-" separators) to create vCard bday con-                                 |
| birthmonth  | bday (partial) | tent<br>Month of birth (MM); prepend with<br>birthyear and append with birthdate<br>(with "-" separators) to create vCard<br>bday content |

<sup>&</sup>lt;sup>1</sup>XEP-0120: Infobits <a href="https://xmpp.org/extensions/xep-0120.html">https://xmpp.org/extensions/xep-0120.html</a>>.

<sup>&</sup>lt;sup>2</sup>RFC 2426: vCard MIME Directory Profile <a href="http://tools.ietf.org/html/rfc2426">http://tools.ietf.org/html/rfc2426</a>>.

<sup>&</sup>lt;sup>3</sup>XEP-0054: vcard-temp <https://xmpp.org/extensions/xep-0054.html>.

<sup>&</sup>lt;sup>4</sup>The XMPP Registrar maintains a list of reserved protocol namespaces as well as registries of parameters used in the context of XMPP extension protocols approved by the XMPP Standards Foundation. For further information, see <a href="https://xmpp.org/registrar/">https://xmpp.org/registrar/</a>.

<sup>&</sup>lt;sup>5</sup>draft-dawson-vcard-xml-dtd-03 <http://www.watersprings.org/pub/id/draft-dawson-vcard-xml-dtd-0 3.txt>. Work in progress.

| Infobit Key | vCard Element  | Comments  |
|-------------|----------------|---|
| birthyear   | bday (partial) | Year of birth (YYYY); append with<br>birthmonth and birthdate (with "-"<br>separators) to create vCard bday con-<br>tent; the vCard "bday" element is<br>separated into three infobits so that<br>users can abstain from providing a<br>birthyear                 |
| cellphone   | tel + cell     | A cellphone (mobile phone) number;<br>if more than one cellphone num-<br>ber is specified, this infobit keyname<br>should be appended with one of the<br>following modifiers: home, work  |
| city        | city           | If more than one address is speci-<br>fied (e.g., work and home), this info-<br>bit keyname may be appended with<br>any of the following address mod-<br>ifiers: home, work, postal, parcel<br>(e.g., city.home)  |
| country     | country        | If more than one address is speci-<br>fied (e.g., work and home), this info-<br>bit keyname may be appended with<br>any of the following address mod-<br>ifiers: home, work, postal, parcel   |
| email       | email          | (e.g., country.home)<br>If more than one email address is<br>specified, this infobit name should be<br>appended with one of the following   |
| extadd      | extadd         | address modifiers: home, work<br>Extended address; if more than one<br>address is specified (e.g., work and<br>home), this infobit keyname may be<br>appended with any of the follow-<br>ing address modifiers: home, work,<br>postal, parcel (e.g., extadd.home) |
| family      | family         | A family name or surname; in some cultures, known as a "last name"  |
| fax         | tel + fax      | A fax number; if more than one fax<br>number is specified, this infobit key-<br>name should be appended with one<br>of the following modifiers: home,   |
| fn          | fn             | work<br>A full name   |
| given       | given          | A given name; in some cultures,<br>known as a "first name"  |

| Infobit Key | vCard Element   | Comments  |
|-------------|-----------------|---|
| key         | key             | This SHOULD be a URL to or identifier                       |
|             |                 | for a public key, but MAY be the key                        |
|             |                 | information itself  |
| lat         | lat             | Latitude in decimal degrees North                           |
| logo        | logo            | This MUST be a URL to a logo; recipi-                       |
|             |                 | ents should be prepared to parse the                        |
|             |                 | URL in order to retrieve and then de-                       |
|             |                 | code the binary information                                 |
| lon         | lon             | Longitude in decimal degrees East                           |
| middle      | middle          | A person's middle name or initial                           |
| nickname    | nickname        | A person's preferred nickname or                            |
| orgnam      | orgnam          | less formal name<br>A name for an organization              |
| orgunit     | orgunit         | A name for an organizational unit                           |
| pager       | tel + pager     | A pager number; if more than one                            |
|             |                 | pager number is specified, this in-                         |
|             |                 | fobit keyname should be appended                            |
|             |                 | with one of the following modifiers:                        |
|             |                 | home, work  |
| pcode       | pcode           | A postal code; if more than one                             |
|             |                 | address is specified (e.g., work and                        |
|             |                 | home), this infobit name may be ap-                         |
|             |                 | pended with any of the following ad-                        |
|             |                 | dress modifiers: home, work, postal,                        |
| ,           | . 1 .           | parcel  |
| phone       | tel + voice     | A voice phone number, if more than                          |
|             |                 | one voice phone number is speci-                            |
|             |                 | fied, this infobit keyname should be                        |
|             |                 | appended with one of the following                          |
| nhata       | photo + extval  | modifiers: home, work<br>This MUST be a URL to a photo; re- |
| photo       | piloto + extvai | cipients should be prepared to parse                        |
|             |                 | the URL in order to retrieve and then                       |
|             |                 | decode the binary information                               |
| prefix      | prefix          | A prefix to a name (e.g., "Dr.")                            |
| region      | region          | If more than one address is speci-                          |
| region      | 1081011         | fied, this infobit keyname may be ap-                       |
|             |                 | pended with any of the following ad-                        |
|             |                 | dress modifiers: home, work, postal,                        |
|             |                 | parcel (e.g., region.home)                                  |
| role        | role            | A person's role within an organiza-                         |
|             | -               | tion  |

| Infobit Key | vCard Element  | Comments   |
|-------------|----------------|--|
| sound       | sound + extval | This MUST be a URL to a sound<br>file; recipients should be prepared to<br>parse the URL in order to retrieve<br>and then decode the binary informa-   |
| street      | street         | tion<br>Street number and name; if more<br>than one address is specified, this in-<br>fobit keyname may be appended with<br>any of the following address mod-<br>ifiers: home, work, postal, parcel<br>(e.g., street.home)   |
| suffix      | suffix         | A suffix to a name (e.g., "Esq.")  |
| title       | title          | This is a job title, and is not to<br>be confused with the Dublin Core<br>Metadata Initiative (DCMI) The<br>Dublin Core Metadata Initiative<br>(DCMI) is an organization dedi-<br>cated to promoting the widespread<br>adoption of interoperable metadata<br>standards. For further information,<br>see <a href="http://www.dublincore.org/">http://www.dublincore.org/</a> >. |
| vmail       | tel + msg      | "title" metadata term<br>A voicemail (message) number; if<br>more than one voicemail number<br>is specified, this infobit keyname<br>should be appended with one of the<br>following modifiers: home, work   |
| website     | url            | URL for any website  |

## 3 Supplementing vCard

The vCard specification does not include the following infobits because either (1) it is not that granular or (2) they represent entities or properties that did not exist when the vCard format was defined.

| Infobit | Comments  |
|---------|---|
| alt     | Altitude in meters above sea level  |
| area    | An area within a locality; if more than one address is specified, this infobit key- |
|         | name may be appended with any of the following address modifiers: home,             |
|         | work, postal, parcel (e.g., area.home)  |

#### ✓ 6 XMPP REGISTRAR CONSIDERATIONS

| Infobit   | Comments   |
|-----------|--|
| building  | The name of a specific building; if more than one address is specified, this infobit |
|           | keyname may be appended with any of the following address modifiers: home,           |
|           | work, postal, parcel (e.g., building.home)   |
| expertise | A self-defined area of expertise (no guarantees provided)                            |
| floor     | The floor of a building; if more than one address is specified, this infobit key-    |
|           | name may be appended with any of the following address modifiers: home,              |
|           | work, postal, parcel (e.g., floor.home)  |
| gender    | The self-defined gender of a user (this is not limited to "male" and "female",       |
|           | although those are the expected values in most instances)                            |
| interest  | A self-defined area of interest  |
| jid       | An entity's Jabber Identifier  |
| orgurl    | URL for organization's website   |
| room      | A specific room; if more than one address is specified, this infobit keyname may     |
|           | be appended with any of the following address modifiers: home, work, postal,         |
|           | parcel (e.g., room.home)   |
| weblog    | URL for weblog   |

## **4** Security Considerations

This document introduces no security considerations above and beyond those already defined in XEP-0120.

### **5 IANA Considerations**

This document requires no interaction with the Internet Assigned Numbers Authority (IANA) <sup>6</sup>.

### 6 XMPP Registrar Considerations

The following is a submission to the infobits registry called for by XEP-0120.

<sup>&</sup>lt;sup>6</sup>The Internet Assigned Numbers Authority (IANA) is the central coordinator for the assignment of unique parameter values for Internet protocols, such as port numbers and URI schemes. For further information, see <a href="http://www.iana.org/>">http://www.iana.org/></a>.

## 6.1 vCard Mapping Infobits

To follow.

## 6.2 vCard Supplement Infobits

To follow.