



XMPP

XEP-0350: Data Forms Geolocation Element

Michael Laukner

<mailto:laukner@gmail.com>

<xmpp:laukner@jabber.org>

2017-09-11

Version 0.2

Status	Type	Short Name
Deferred	Standards Track	geolocation-element

This specification defines an XMPP protocol extension for including geolocation data in XEP-0004 data forms.

Legal

Copyright

This XMPP Extension Protocol is copyright © 1999 – 2017 by the [XMPP Standards Foundation](#) (XSF).

Permissions

Permission is hereby granted, free of charge, to any person obtaining a copy of this specification (the "Specification"), to make use of the Specification without restriction, including without limitation the rights to implement the Specification in a software program, deploy the Specification in a network service, and copy, modify, merge, publish, translate, distribute, sublicense, or sell copies of the Specification, and to permit persons to whom the Specification is furnished to do so, subject to the condition that the foregoing copyright notice and this permission notice shall be included in all copies or substantial portions of the Specification. Unless separate permission is granted, modified works that are redistributed shall not contain misleading information regarding the authors, title, number, or publisher of the Specification, and shall not claim endorsement of the modified works by the authors, any organization or project to which the authors belong, or the XMPP Standards Foundation.

Warranty

NOTE WELL: This Specification is provided on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE.

Liability

In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall the XMPP Standards Foundation or any author of this Specification be liable for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising from, out of, or in connection with the Specification or the implementation, deployment, or other use of the Specification (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if the XMPP Standards Foundation or such author has been advised of the possibility of such damages.

Conformance

This XMPP Extension Protocol has been contributed in full conformance with the XSF's Intellectual Property Rights Policy (a copy of which can be found at <https://xmpp.org/about/xsf/ipr-policy>) or obtained by writing to XMPP Standards Foundation, P.O. Box 787, Parker, CO 80134 USA).

Contents

1	Introduction	1
2	Requirements	1
3	Integrate Geolocation Element with XEP-0004	1
4	Allow Receiver to Validate Geolocation Data	2
4.1	Location Datatypes for Data Forms	3
5	Security Considerations	3
6	IANA Considerations	3
7	XMPP Registrar Considerations	3
7.1	Protocol Namespaces	3
7.2	Location Fields and Data Form Validation Datatypes	4
7.3	Text Field and Data Form Validation Datatypes	4
8	XML Schema	5

1 Introduction

In certain protocols that make use of [Data Forms \(XEP-0004\)](#)¹, it can be helpful to include geolocation data. One example of such a "using protocol" is [Form Discovery and Publishing \(XEP-0346\)](#)². This document defines a method for including geolocation data in a Data Form for something you manage and want to publish. This XEP leaves it open to developers how such a <geoloc/> form element will be rendered; possibilities might include editing Latitude and Longitude manually or through a rendered map.

There may also be the need to gather location data from both humans (using a GUI format) and computer processes (using a pre-defined but flexible format). This document defines a flexible mechanism for the [XMPP Registrar](#)³ to standardize geographical location field names in data forms, thus enabling XMPP clients to process location fields in forms while giving protocol authors a way to specify additional location data types for non-GUI processors to determine the semantic meanings of a location field.

2 Requirements

This proposal addresses the following requirements:

- Integrate geolocation data with XEP-0004.
- Allow a potential receiver (rather than the sender) to validate geolocation data.

3 Integrate Geolocation Element with XEP-0004

The root element for geolocation data is <geoloc/> as defined in [User Geolocation \(XEP-0080\)](#)⁴. The information is structured by means of a <geoloc/> element that is qualified by the 'http://jabber.org/protocol/geoloc' namespace. The <geo/> element MUST be contained within a <field/> element qualified by the 'jabber:x:data' namespace.

The following example is provided only for the purpose of illustration; consult the specifications for using protocols (e.g., XEP-0080) to see canonical examples.

Listing 1: Inclusion in Data Form

```
<x xmlns='jabber:x:data' type='form'>
  [ ... ]
  <field var='location'>
```

¹XEP-0004: Data Forms <<https://xmpp.org/extensions/xep-0004.html>>.

²XEP-0346: Form Discovery and Publishing <<https://xmpp.org/extensions/xep-0346.html>>.

³The XMPP Registrar maintains a list of reserved protocol namespaces as well as registries of parameters used in the context of XMPP extension protocols approved by the XMPP Standards Foundation. For further information, see <<https://xmpp.org/registrar/>>.

⁴XEP-0080: User Geolocation <<https://xmpp.org/extensions/xep-0080.html>>.

```

    <geoloc xmlns="http://jabber.org/protocol/geoloc">
      <text>Venice, Italy</text>
      <locality>Venice</locality>
      <country>Italy</country>
      <lat>45.44</lat>
      <lon>12.33</lon>
    </geoloc>
  </field>
  [ ... ]
</x>

```

4 Allow Receiver to Validate Geolocation Data

All elements associated with location fields MUST be qualified by the 'http://jabber.org/protocol/geoloc' namespace. The use of namespace prefixes is RECOMMENDED for large forms, to reduce the data size. To maintain the highest level of compatibility, implementations sending the form using prefixes SHOULD use the namespace prefix "geo:", and SHOULD declare the namespace prefix mapping in the ancestor <xmlns='jabber:x:data'/> element:

The following example is provided only for the purpose of illustration; consult the specifications for using protocols (e.g. XEP-0080, XEP-0122) to see canonical examples.

Listing 2: Validation of Geolocation Data

```

<x xmlns='jabber:x:data'
  xmlns:geo='http://jabber.org/protocol/geoloc'
  xmlns:xdv='http://jabber.org/protocols/xdata-validate'
  type='form'>
  <title>Sample_Location_Form</title>
  <instructions>
    Please provide information for the following location fields...
  </instructions>
  <field_type='text-single' _var='name' _label='Event Name' />
  <field_type='text-single' _var='time' _label='Event Date/Time'>
    <xdv:validate_datatype='xs:dateTime'>
      <basic/>
    </xdv:validate>
  </field>
  <field_type='text-single' _var='latitude' _label='Latitude'>
    <xdv:validate_datatype='geo:lat'>
      <basic/>
    </xdv:validate>
  </field>
  <field_type='text-single' _var='longitude' _label='Longitude'>
    <xdv:validate_datatype='geo:lon'>
      <basic/>
    </xdv:validate>
  </field>

```

```
.....</xdt:validate>
..</field>
</x>
```

4.1 Location Datatypes for Data Forms

The integration with Data Forms is accomplished via the datatypes specified in [Data Forms Validation \(XEP-0122\)](#)⁵. Each datatype is specific to the profile desired. The sender MUST use the 'geo:' datatypes as specified in XEP-0122. When submitting a form, a field's value(s) MUST be validated by the receiving entity based on the 'geo:' datatype identifier(s). Also, the submitter MUST provide a 'geo:' element for each location element within the data form. If a form-submitting entity receives a field type it does not understand, the 'text-single' field type from XEP-0004 MUST be assumed.

5 Security Considerations

It is imperative to control access to location information, at least by default. Imagine that a stalker got unauthorized access to this information, with enough accuracy and timeliness to be able to find the target person. This scenario could lead to loss of life, so please take access control checks seriously. If an error is deliberately added to a location, the error SHOULD be the same for all receivers, to minimize the likelihood of triangulation. In the case of deliberate error, the <accuracy /> element SHOULD NOT be included.

6 IANA Considerations

This document requires no interaction with the the [Internet Assigned Numbers Authority \(IANA\)](#)⁶.

7 XMPP Registrar Considerations

7.1 Protocol Namespaces

The [XMPP Registrar](#)⁷ already includes 'http://jabber.org/protocol/geoloc' in its registry of protocol namespaces (see <<https://xmpp.org/registrar/namespaces.html>>).

⁵XEP-0122: Data Forms Validation <<https://xmpp.org/extensions/xep-0122.html>>.

⁶The Internet Assigned Numbers Authority (IANA) is the central coordinator for the assignment of unique parameter values for Internet protocols, such as port numbers and URI schemes. For further information, see <<http://www.iana.org/>>.

⁷The XMPP Registrar maintains a list of reserved protocol namespaces as well as registries of parameters used in the context of XMPP extension protocols approved by the XMPP Standards Foundation. For further information, see <<https://xmpp.org/registrar/>>.

7.2 Location Fields and Data Form Validation Datatypes

The XMPP Registrar includes 'geo:' in its registry of Data Forms Validation Datatype Prefixes. Normally, each geographic format that wishes to be considered for use with Data Forms MUST register its own datatype qualified by the "geo:" prefix. However, this document provides an initial seed, based on the currently assumed formats. The following datatypes shall be registered for use with Data Forms Validation:

```
<datatype>
  <name>geo:lat</name>
  <desc>Datatype for publishing the latitude of a geographic location<
    /desc>
  <doc>XEP-0080</doc>
</datatype>
```

Listing 3: Validation of a XEP-0080 Latitude Field

```
<field type='text-single' var='latitude' label='Latitude'>
  <xdv:validate datatype='geo:lat'>
    <range min='-90'
      max='90' />
  </xdv:validate>
  <value>45.44</value>
</field>
```

```
<datatype>
  <name>geo:lon</name>
  <desc>Datatype for publishing the longitude of a geographic location
    </desc>
  <doc>XEP-0080</doc>
</datatype>
```

Listing 4: Validation of XEP-0080 Longitude Field

```
<field type='text-single' var='longitude' label='Longitude'>
  <xdv:validate datatype='geo:lon'>
    <range min='-180'
      max='180' />
  </xdv:validate>
  <value>12.33</value>
</field>
```

7.3 Text Field and Data Form Validation Datatypes

The XMPP Registrar MAY include 'geo:' datatypes in its registry of Data Forms Validation Datatypes, which can be used with the 'text-single' field type from XEP-0004.

```

<datatype>
  <name>geo:dms</name>
  <desc>Datatype for publishing a degrees, minutes, and seconds (DMS)
    location</desc>
  <doc>Degree Minutes and Seconds, 'http://en.wikipedia.org/wiki/
    Geographic\_coordinate\_system'.</doc>
</datatype>

```

Listing 5: Validation of a DMS Location Field

```

<field type='text-single' var='dms_location'>
  <xdv:validate datatype='geo:dms' />
  <regex>([-|\\+]?\\d{1,3}[d|D|\\u00B0|\\s](\\s*\\d{1,2}['|\\u2019|\\s
    ])?(\\s*\\d{1,2}[\\\"|\\u201d])?\\s*[N|n|S|s]?)(\\s*|,|,\\s*)
    ?([-|\\+]?\\d+?(\\.|\\d+)?)?\\s*[E|e|W|w]?)</regex>
</xdv:validate>
<value>52d18'24.4775"N_0d52'44.0625"W</value>
</field>

```

```

<datatype>
  <name>geo:mgrs</name>
  <desc>Datatype for publishing a MGRS location</desc>
  <doc>Military Grid Reference System, 'http://en.wikipedia.org/wiki/
    Military\_grid\_reference\_system'.</doc>
</datatype>

```

Listing 6: Validation of a MGRS Location Field

```

<field type='text-single' var='mgrs_location'>
  <xdv:validate datatype='geo:mgrs' />
  <regex>\\d{1,2}[A-Za-z]\\s*[A-Za-z]{2}\\s*\\d{1,5}\\s*\\d{1,5}</
    regex>
</xdv:validate>
<value>38SMB4484</value>
</field>

```

8 XML Schema

As this document only defines semantics for existing protocol, additional schemas are not required.